

PDU Technology Specification

Date: 03/01/2021

NO.: DBAL0312103005

Customer	AL	RoHS	Yes
Product Name	Designated Power Distribution Unit for Cabinet	Customer's Code	
Part Number	AUE2220B1-06AHENMB	Picture Code	DBAL0312103005
No.	Item	Detailed Description	
1	Product Series	AUE2220	
2	Socket Type	BS1363(90degree) Outlet Module[6];	
3	Socket Quantity	6	
4	Power Input	Left end single input	
5	Bracket Install	Frontal installation	
6	Cable with plug	IEC60309 plug (16A 2P+E)	
7	Control Function	No controlling function	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3 x 2.5 mm ² x 1.8M	
11	Product Size	L x W x H = 492 x 44.4 x 62 mm	
12	Mounting Length	466 mm	
13	Case Length	436 mm	
14	PDU Exponent	0.983	
15	Fittings	2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut,	
16	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	AUE2220B1-06AHENMB
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety Authentication	CE
		Logo	RoHS
		Producer	
No.	Add-In		
1	Socket assemble	No	
2	Interior Connection Wire	1.5 mm ² (16AWG)	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp(11)	
5	Module Assemble (from left to right)	Pls refer to the drawing	
6	Others		
Made by: Linda		Customer confirm:	Check: Authorize:

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

Preview



IEC60309 plug (16A 2P+E)

DIMENSION AND TOLERANCES (Unit: mm)			SHENZHEN CLEVER ELECTRONIC CO.,LTD	
Length: 492	Mounting length: 466		Customer	AL
Width: 44.4	Case length: 436		Product name	Designated Power Distribution Unit for Cabinet
Height: 62	case tolerance: ± 1.0		Part number	AUE2220B1-06AHENMB
	SIGN	DATE	Customer's code	
DRAWN	Linda	03/01/2021	Drawing number	DBAL0312103005
CHK'D			Edition number	
APP'D				